

Transparent Testing & Simplified Measurement

Contact Resistance Meter SBE - CRM 200 2RE - CKM 500

















SPECIAL FEATURES

- True Four Terminal Measurement.
- 200 Amp. DC Constant Current Source.
- 3.5 Digit LCD / LED Display.
- **1** μ Ω resolution.
- Fast response Time.
- Stable and Fast Measurement.

APPLICATION FIELD

- Circuit Breakers.
- Isolators.
- Busbars Component Manufacturer.
- Current Transformer Manufacturer.
- Cable & Joints.
- College Laboratories.

PRODUCT FEATURE

- High current: For latest power supply technology, the tester can continuously output high current which overcomes the weakness Of instantaneous current produced by pulsed power. It can effectively breakdown/puncture the oxide layer of the switches and then get precise results.
- Strong anti-interference ability: The last number of test data will stably show in the LCD screen only with ±1 error even in strong Interference situation.
- Long service life: All the precise resistances used in the tester can reduce the temperature's impact on the measurement results and military connectors can enhance vibration resistance.
- Convenience: Small size, light weight.

Technical Specification:

MEASUREMENT RANGE :	0~1999 μΩ
RESOLUTION:	1μΩ
MEASURED CURRENT :	DC 200A
ACCURACY:	± (0.5% rd + 2d)
CONTINOUS WORKING TIME :	5 Sec - 599 Sec
DISPLAY	3.5 LCD
COMMUNICATION MODE	USB
POWER SUPPLY :	AC 220 V +/- 10%, 50 Hz
SERVICE CONDITION:	TEMP: 10 - 50 deg. C, Humidity: <80% RH
DIMENSION:	350 mm X 320 mm X 260 mm
WEIGHT:	9 KG (NOT INCLUDING ACCESSORY)











OUR PRODUCT IS SERVING THROUGHOUT THE GLOBE CONNECT WITH US











Transparent Testing & Simplified Measurement

S.B.ELECTROTECH

124, SIKDAR PARA, RAJPUR, KOLKATA, **ZIP CODE: 700 149, WEST BENGAL, INDIA**

Ph.: +91-7278354202, +91-9477423085

Website: www.sbelectrotech.org

Email Id: info@sbelectrotech.org || sales@sbelectrotech.org

